

**Claims**

1. Device for cleaning of an air stream (40) from electrically charged particles (aerosols), said air stream  
5 passing through the device, said device comprising at least two electrode elements (20, 21) that are arranged in planes parallel to each other and at a gap distance (d) between adjacent electrode elements (20, 21), that the electrode elements (20, 21) are connected to a respective terminal of a  
10 high voltage source, and that spacers (11) are provided between adjacent electrode elements (20, 21),  
c h a r a c t e r i s e d in that the spacers (11) constitute electrically insulating material, through which material the air stream may pass, and that the spacers (11) are arranged in  
15 such a way that all air transport through the device must pass through the spacers (11).
2. Device according to claim 1, c h a r a c t e r i s e d in that the spacers (11) that belong to one gap are arranged in  
20 V-shape.
3. Device according to claim 1 or 2,  
c h a r a c t e r i s e d in that the spacers (11) along their entire length abut to adjacent electrode elements (20,  
25 21).
4. Device according to any of the previous claims,  
c h a r a c t e r i s e d in that the spacers (11) generally extend along the direction of the air stream through the  
30 device.
5. Device according to any of the previous claims,  
c h a r a c t e r i s e d in that the spacers (11) constitute glass fibre or synthetic fibre.  
35
6. Device according to any of the claims 1-4,  
c h a r a c t e r i s e d in that the spacers (11) constitute foamed plastic.

7. Device according to any of the previous claims,  
c h a r a c t e r i s e d in that the gap (d) is in the  
interval 3-30 mm.
- 5 8. Device according to any of the previous claims,  
c h a r a c t e r i s e d in that the passage area (12) of  
two cooperating spacers (11) should be at least double the  
available inlet area (41) of the air stream when it passes  
between two adjacent electrode elements (20, 21).
- 10 9. Device according to any of claims 1-5,  
c h a r a c t e r i s e d in that the spacers (11) are  
manufactured from materials having high heat resistance, e.g.  
ceramic materials.
- 15 10. Device according to claim 9, c h a r a c t e r i s e d  
in that also the electrode elements (20, 21) constitute heat  
resistant material, e.g. aluminium.
- 20 11. Device according to any of the claims 1-5,  
c h a r a c t e r i s e d in that the electrode elements (20,  
21) consist of a high resistive material or have a coating of  
high resistive material.
- 25 12. Device according to claim 11, c h a r a c t e r i s e d  
in that the electrode elements (20, 21) constitute cellulose  
material.
- 30 13. Device according to any of the previous claims,  
c h a r a c t e r i s e d in that the spacers (11) and the  
electrode elements (20, 21) are surrounded by a cover on the  
sides having an extension in the direction of the air stream.